



Published by:
Pattimura University
In Collaboration with:
Indonesian Mathematical Society (IndoMS)

Barekeng


jurnal ilmu matematika dan terapan

BAREKENG : JURNAL ILMU MATEMATIKA DAN TERAPAN
BAREKENG : JOURNAL OF MATHEMATICS AND ITS APPLICATION



ISSN : 1978 - 7227 (Print)
ISSN : 2615 - 3017 (Online)

HOME / ARCHIVES / Vol 16 No 3 (2022): BAREKENG: Jurnal Ilmu Matematika dan Terapan



BAREKENG : Journal of Mathematics and Its Applications, volume 16 issue 3 (September 2022) was officially published in English (also journal name officialy in english). BAREKENG : Journal of Mathematics and Its Applications, has been published four (4) times a year in March, June, September, and December (4 issues). This issue contain 40 articles available online and consists of authors from 3 countries (Indonesia, Malaysia and Nigeria).

DOI: <https://doi.org/10.30598/barekengvol16iss3year2022>

PUBLISHED: 2022-09-01

Accredited By:

Ministry of Education Culture, Research, and Technology, Republic of Indonesia, based on the Decree No.: 158/E/KPT/2021, about Accreditation Rank of Scientific Journal 2021, announce that BAREKENG: Jurnal Ilmu Matematika dan Terapan has been accredited in SINTA 2 (see detail)

Accredited

SINTA 2



In Collaboration with:



BAREKENG: Jurnal ilmu matematika dan terapan, published by Pattimura University, in Collaboration with Indonesian Mathematical Society (IndoMS). (see detail)

Indexed By:



Editorial Team



B. P. Tomasouw, S.Si, M.Si
(Layout/Production Editor)

About Journal

BAREKENG: Jurnal ilmu Matematika dan Terapan (p-ISSN: 1978-7227 and e-ISSN: 2615-3017) is a scientific publication media, which published by Mathematics

Articles

ANALYSIS OF THE VACCINATION'S IMPACT ON THE INCREASE IN COVID-19'S DAILY NEW AND RECOVERED CASES USING THE VECTOR AUTOREGRESSIVE (VAR) MODEL (CASE STUDY: WEST KALIMANTAN)

Yundari Yundari, Nur'ainul Miftahul Huda

761-770

pdf download

Abstract views 44 | PDF Download downloads 46 | DOI <https://doi.org/10.30598/barekengvol16iss3pp761-770>

CLASSIFICATION OF STUNTING IN CHILDREN UNDER FIVE YEARS IN PADANG CITY USING SUPPORT VECTOR MACHINE

Izzati Rahmi, Mega Susanti, Hazmira Yoza, Frilianda Wulandari

771-778

pdf download

Abstract views 51 | PDF Download downloads 44 | DOI <https://doi.org/10.30598/barekengvol16iss3pp771-778>

RIDGE LEAST ABSOLUTE DEVIATION PERFORMANCE IN ADDRESSING MULTICOLLINEARITY AND DIFFERENT LEVELS OF OUTLIER SIMULTANEOUSLY

Netti Herawati, Subian Saidi, Dorrah Azis

779-786

pdf download

Abstract views 29 | PDF Download downloads 32 | DOI <https://doi.org/10.30598/barekengvol16iss3pp779-786>

CALCULATION OF CREDITED INTEREST RATE WITH INVESTMENT YEAR METHOD AND PORTFOLIO METHOD

Jevilia Aryento, Felivia Kusnadi, Dharma Lesmono

787-796

pdf download

Abstract views 47 | PDF Download downloads 34 | DOI <https://doi.org/10.30598/barekengvol16iss3pp787-796>

OUTLIER DETECTION ON HIGH DIMENSIONAL DATA USING MINIMUM VECTOR VARIANCE (MVV)

Andi Harismahyanti A., Indahwati Indahwati, Anwar Fitrianto, Erfiani Erfiani

797-804

pdf download

Abstract views 44 | PDF Download downloads 34 | DOI <https://doi.org/10.30598/barekengvol16iss3pp797-804>

ONE-DIMENSIONAL CUTTING STOCK PROBLEM THAT MINIMIZES THE NUMBER OF DIFFERENT PATTERNS

Bib Paruhum Silalahi, Farida Hanum, Fajar Setyawan, Prapto Tri Supriyo

805-814

pdf download

Abstract views 55 | PDF Download downloads 33 | DOI <https://doi.org/10.30598/barekengvol16iss3pp805-814>

THE BAYESIAN SEM APPROACH ON RELIGIOUS TOURISM AND SME'S ENTREPRENEURIAL OPPORTUNITY INTERRELATION IN RURAL AREA

Frilienda Wulandari, Dodi Devianto, Ferrá Yanuar

815-828

[pdf download](#)

Abstract views 38 | Pdf Download downloads 21 | DOI <https://doi.org/10.30598/barekengvol16iss3pp815-828>

AN EXISTENCE AND UNIQUENESS OF THE WEAK SOLUTION OF THE DIRICHLET PROBLEM WITH THE DATA IN MORREY SPACES

Nicky Kurnia Tumalun

829-834

[pdf download](#)

Abstract views 39 | Pdf Download downloads 44 | DOI <https://doi.org/10.30598/barekengvol16iss3pp829-834>

OPTIMAL CONTROL OF INFLUENZA A DYNAMICS IN THE EMERGENCE OF A TWO STRAIN

Jonner Nainggolan

835-844

[pdf download](#)

Abstract views 41 | Pdf Download downloads 32 | DOI <https://doi.org/10.30598/barekengvol16iss3pp835-844>

TAGUCHI METHOD APPLIED FOR THE INVESTIGATION OF CORROSION LEVEL ON METAL INERT GAS WELDING OF MILD STEEL

Nanang Fatchurrohman, Low Tze Chin, Jufriadif Na'am

845-852

[pdf download](#)

Abstract views 36 | Pdf Download downloads 35 | DOI <https://doi.org/10.30598/barekengvol16iss3pp845-852>

AN ORDINAL LOGISTIC REGRESSION MODEL FOR ANALYZING RISK ZONE STATUS OF COVID-19 SPREAD

Tessya Mutiara Dewi, Rosita Kusumawati

853-860

[pdf download](#)

Abstract views 37 | Pdf Download downloads 26 | DOI <https://doi.org/10.30598/barekengvol16iss3pp853-860>

MULTILEVEL NON-LINIER REGRESSION FOR REPEATED MEASUREMENT DATA AS STUDY OF PEANUT GROWTH

Arie Purwanto, Umul Aiman

861-868

[pdf download](#)

Abstract views 49 | Pdf Download downloads 29 | DOI <https://doi.org/10.30598/barekengvol16iss3pp861-868>

ON THE IRREGULARITY STRENGTH AND MODULAR IRREGULARITY STRENGTH OF FRIENDSHIP GRAPHS AND ITS DISJOINT UNION

Fredrylo Alberth Noel Joddy Apituley, Mozart W. Talakua, Yopi Andry Lesnussa

869-876

[pdf download](#)

Abstract views 25 | Pdf Download downloads 18 | DOI <https://doi.org/10.30598/barekengvol16iss3pp869-876>

FUZZY LOGIC APPLICATION ON EMPLOYEE ACHIEVEMENT ASSESSMENT (CASE STUDY: EDUCATION QUALITY ASSURANCE INSTITUTE OF MALUKU PROVINCE)

Nurhidayah Nurhidayah, Yopi Andry Lesnussa, Zeth Arthur Leleury

877-886

[pdf download](#)

Abstract views 30 | Pdf Download downloads 22 | DOI <https://doi.org/10.30598/barekengvol16iss3pp877-886>

QUOTIENT SEMINEAR-RINGS OF THE ENDOMORPHISM OF SEMINEAR-RINGS

Meryta Febrilian Fatimah, Fitriana Hasnani, Nikken Prima Puspita

887-896

[pdf download](#)

Abstract views 45 | Pdf Download downloads 24 | DOI <https://doi.org/10.30598/barekengvol16iss3pp887-896>

SURVIVAL ANALYSIS OF DENGUE HEMORRHAGIC FEVER PATIENTS (DHF)

Firza Khairunnisa, Fazrina Saumi, Amelia Amelia

897-908

[pdf download](#)

Abstract views 49 | Pdf Download downloads 26 | DOI <https://doi.org/10.30598/barekengvol16iss3pp897-908>

ON COMPUTATIONAL BAYESIAN ORDINAL LOGISTIC REGRESSION LINK FUNCTION IN CASES OF CERVICAL CANCER IN TUBAN

Nur Mahmudah, Fetrika Anggraini

909-918

[pdf download](#)

Abstract views 31 | Pdf Download downloads 24 | DOI <https://doi.org/10.30598/barekengvol16iss3pp909-918>

Department, Faculty of Mathematics and Natural Sciences, University of Pattimura. This journal publish article related to Pure Mathematics, Applied Mathematics, Statistics, Actuarial Science, Mathematic Computation and Mathematics Education.

The meaning word of **Barekeng** is a local term of Moluccas language which means **Counting** or **Calculating**. Counting is a main and fundamental activities in the field of Mathematics. Therefore we tried to promote "**Barekeng**" as the name of our scientific journal.

[Read more...](#)

Journal Statistics

Visitors



Pageviews: 212,491

FLAG counter



[View My Stats](#)

Updates Information

Good News!!!

Since 2020, BAREKENG: Journal of Mathematics and Its Applications, published four times a year, in March, June, September, and December.

The articles for Volume 16 issue 3, September 2022 had been published with authors from 3 countries (Indonesia, Malaysia & Nigeria), while for Volume 16 issue 4 December 2022 are in process. Now, BAREKENG: Journal of Mathematics and Its Applications, call for papers to Volume 17 issue 1, March 2023.

Google Scholar Citation

Analysis Citation

All	Since 2
-----	---------

COMPARISON OF ARIMA AND GARMA'S PERFORMANCE ON DATA ON POSITIVE COVID-19 CASES IN INDONESIA

Ayunin Sofro, Khusnia Nurul Khikmah

919-926

pdf download

Abstract views 49 | Pdf Download downloads 38 | DOI <https://doi.org/10.30598/barekengvol16iss3pp919-926>

PERFORMANCE COMPARISON OF GRADIENT-BASED CONVOLUTIONAL NEURAL NETWORK OPTIMIZERS FOR FACIAL EXPRESSION RECOGNITION

Sri Nurdianti, Mohamad Khoirun Najib, Fahren Bukhari, Refi Revina, Fitra Nuvus Salsabila

927-938

pdf download

Abstract views 46 | Pdf Download downloads 70 | DOI <https://doi.org/10.30598/barekengvol16iss3pp927-938>

TEXT CLUSTERING ONLINE LEARNING OPINION DURING COVID-19 PANDEMIC IN INDONESIA USING TWEETS

Maulida Fajrining Tyas, Anang Kumia, Agus Mohamad Soleh

939-948

pdf download

Abstract views 39 | Pdf Download downloads 29 | DOI <https://doi.org/10.30598/barekengvol16iss3pp939-948>

MULTI-RESPONSE OPTIMIZATION OF DIELECTRIC FLUID MIXTURE IN EDM USING GREY RELATIONAL ANALYSIS (GRA) IN TAGUCHI METHOD

Veniola Forestryani, Niam Rosyadi, Muhammad Ahsan

949-960

pdf download

Abstract views 39 | Pdf Download downloads 26 | DOI <https://doi.org/10.30598/barekengvol16iss3pp949-960>

THE HARMONIC INDEX AND THE GUTMAN INDEX OF COPRIME GRAPH OF INTEGER GROUP MODULO WITH ORDER OF PRIME POWER

Muhammad Naoval Husni, Hanna Syafitri, Ayes Malona Siboro, Abdul Gazir Syarifudin, Qurratul Aini, I Gede Adhitya Wisnu Wardhana

961-966

pdf download

Abstract views 85 | Pdf Download downloads 35 | DOI <https://doi.org/10.30598/barekengvol16iss3pp961-966>

ANALYSIS OF THE SPRUCE BUDWORM MODEL USING THE HEUN METHOD AND THIRD-ORDER RUNGE-KUTTA

Irwan Irwan, Muh Irwan, Rosmaniar Rosmaniar, Wahidah Alwi, Risnawati Ibnas

967-974

pdf download

Abstract views 27 | Pdf Download downloads 24 | DOI <https://doi.org/10.30598/barekengvol16iss3pp967-974>

AN ITERATIVE PROCEDURE FOR OUTLIER DETECTION IN GSTAR(1;1) MODEL

Nur'ainul Miftahul Huda, Utriweni Mukhaiyar, Nurfitri Imro'ah

975-984

pdf download

Abstract views 37 | Pdf Download downloads 22 | DOI <https://doi.org/10.30598/barekengvol16iss3pp975-984>

BINARY LOGISTICS REGRESSION MODEL TO IDENTIFY FACTORS ASSOCIATED WITH LOW BIRTH WEIGHT (LBW) (CASE STUDY: BABY DATA AT DR. M. HAULUSSY HOSPITAL AMBON)

Yunita Puspita Sari, Marlon S. Noya Van Delsen, Yopi Andry Lesnussa

985-994

pdf download

Abstract views 28 | Pdf Download downloads 24 | DOI <https://doi.org/10.30598/barekengvol16iss3pp985-994>

CONTROL CHART AS VERIFICATION TOOLS IN TIME SERIES MODEL

Nurfitri Imro'ah, Nur'ainul Miftahul Huda

995-1002

pdf download

Abstract views 26 | Pdf Download downloads 23 | DOI <https://doi.org/10.30598/barekengvol16iss3pp995-1002>

SPATIO-TEMPORAL ANALYSIS OF RUPIAH LOANS PROVIDED BY COMMERCIAL BANKS AND RURAL BANKS

Muktar Redy Susila

1003-1012

pdf download

Abstract views 27 | Pdf Download downloads 25 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1003-1012>

THE INTERSECTION GRAPH REPRESENTATION OF A DIHEDRAL GROUP WITH PRIME ORDER AND ITS NUMERICAL INVARIANTS

Dewi Santri Ramdani, I Gede Adhitya Wisnu Wardhana, Zatta Yumni Awanis

1013-1020

pdf download

Abstract views 75 | Pdf Download downloads 28 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1013-1020>

Citations	1062
h-index	16
i10-index	29

Google Scholar [Chart](#) [Cite](#)

Find us on



Map of Location





DESIGN OF ROV STRAIGHT MOTION CONTROL USING PROPORTIONAL SLIDING MODE CONTROL METHOD

Firman Yudianto, Teguh Herlambang, Fajar Annas Susanto, Andy Suryowinoto, Bery Pebo Tomasouw

1051-1058

 pdf download

 Abstract views 25 |  Pdf Download downloads 26 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1051-1058>

MULTIPLE STRATEGIES AS OPTIMAL CONTROL OF A COVID-19 DISEASE WITH QUARANTINE AND USING HEALTH MASKS

Lukman Hakim

1059-1068

 pdf download



 Abstract views 46 |  Pdf Download downloads 35 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1059-1068>

THE PROPERTIES OF ROUGH V-COEFACT SEQUENCE IN ROUGH GROUP

Desfan Hafifullah, Fitriani Fitriani, Ahmad Faisol

1069-1078

 pdf download



 Abstract views 49 |  Pdf Download downloads 31 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1069-1078>

ESTIMATION OF THIRD FINGER MOTION USING ENSEMBLE KALMAN FILTER

Teguh Herlambang, Hendro Nurhadi, Abdul Muhith, Dinita Rahmalia, Bery Pebo Tomasouw

1079-1086


 pdf download

 Abstract views 25 |  Pdf Download downloads 23 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1079-1086>

APPLICATION FUZZY MAMDANI TO DETERMINE THE RIPENESS LEVEL OF CRYSTAL GUAVA FRUIT

Ahmad Kamsyakawuni, Abduh Riski, Anisa Binti Khumairoh

1087-1096

 pdf download

 Abstract views 31 |  Pdf Download downloads 20 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1087-1096>

CENTRALITY MEASURES ON BRINKMANN GRAPH: BEFORE AND AFTER NODE DELETION

Masrutullaily Masrutullaily

1097-1104

 pdf download

 Abstract views 32 |  Pdf Download downloads 26 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1097-1104>

FINANCIAL DISTRESS PREDICTION OF FINANCIAL SECTOR SERVICE COMPANIES ON INDONESIAN STOCK EXCHANGE USING COX PROPORTIONAL HAZARD

Candra Yanuar Dwi Putra, Mohamat Fatekurohman, Dian Anggraeni

1105-1114

 5006

 Abstract views 41 |  5006 downloads 24 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1105-1114>

ANALYTICAL HIERARCHY PROCESS IN DETERMINING LEVEL THE FEASIBILITY OF THE AUTOMATED TELLER MACHINE LOCATION (CASE STUDY BANK SYARIAH INDONESIA JEMBER)

Agustina Pradjaningsih, Dyan Mei Anggraeni, Kiswara Agung Santoso

1115-1122

 pdf download

 Abstract views 35 |  Pdf Download downloads 31 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1115-1122>

NUMERICAL SOLUTION OF VOLTERRA INTEGRO-DIFFERENTIAL EQUATIONS BY AKBARI-GANJI'S METHOD

O. A. Uwaheren, A. F. Adebisi, C. Y. Ishola, M. T. Raji, A. O. Yekeem, O. J. Peter

1123-1130

 pdf download

 Abstract views 72 |  PDF Download downloads 32 | DOI <https://doi.org/10.30598/barekengvol16iss3pp1123-1130>

Editorial Office

Pattimura University

Ex. UT Building 2nd Floor, Ir. M. Putuhena Street,
Poka-Ambon City, 97233, Maluku Province, Indonesia

Contact Info

+62 852 4335 8669 (Yopi Andry Lesnussa)

+62 823 9798 0021 (Dyana Patty)

barekeng.journal@mail.unpatti.ac.id

barekeng.math@yahoo.com

Platform &
workflow by


APPLICATION FUZZY MAMDANI TO DETERMINE THE RIPENESS LEVEL OF CRYSTAL GUAVA FRUIT

Ahmad Kamsyakawuni^{1*}, Abduh Riski², Anisa Binti Khumairoh³

^{1,2,3}Department of Mathematics, Faculty of Mathematics and Natural Science, Jember University

^{1,2}MOCO Research Group, Faculty of Mathematics and Natural Science, Jember University
Kalimantan St., No.37, Kampus Tegalboto, Jember, 68121, Indonesia

Corresponding author's e-mail: ^{1*} kamsyakawuni.fmipa@unej.ac.id

Abstract. Crystal guava is one of Indonesia's flora diversities. The rind of the unripe crystal guava fruit is green, and the rind of the ripe crystal guava fruit is yellowish green. However, it is difficult to determine the ripeness of crystal guava due to the similar color of the fruit skin. Determining fruit ripeness is uncertain and therefore requires a way to deal with this uncertainty. One of the methods you can use is fuzzy Mamdani. In this study, the ripeness level of crystal guava is determined using fuzzy Mamdani. Crystal guava fruits fall into four ripeness categories: raw, half ripe, ripe, and very ripe. The data used is in the form of an RGB image separated from the background so that only crystal guava fruit objects are captured. The image of the fruit object was then extracted by looking for the median red, green, and blue at each pixel of the image. This value is used as input for the fuzzy Mamdani process. The fuzzy set and fuzzy rules that have been formed can be applied to determine the maturity level of crystal guava fruit by validating the results of 140 image data with an accuracy of 83,5%.

Keywords: Crystal Guava Fruit, Fuzzy Mamdani, RGB Image, Ripeness Level

Article info:

Submitted: 17th July 2022

Accepted: 28th August 2022

How to cite this article:

A. Kamsyakawuni, A. Riski and A. B. Khumairoh, "APPLICATION FUZZY MAMDANI TO DETERMINE THE RIPENESS LEVEL OF CRYSTAL GUAVA FRUIT", *BAREKENG: J. Math. & App.*, vol. 16, iss. 3, pp. 1087-1096, September, 2022.



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).
Copyright © 2022 Author(s)

1. INTRODUCTION

Indonesia is a country with a tropical climate that has a diversity of flora. Crystal guava is one of the diversities of flora in Indonesia. This type of guava has advantages such as the relatively small number of seeds ranging from 3% of the fruit size [1]. This fruit also has a crunchy flesh texture and a fresh sweet taste [2]. Farmers prefer this variety of guava because it is simple to grow and can produce fruit all year long [3]. This fruit has a high selling value compared to other varieties of guava [4]. People used to use crystal guava fruit from raw to ripe.

The process of determining the ripeness of crystal guava fruit is usually done manually by paying attention to the color of the fruit's skin. Crystal guava fruit that is still raw has green skin, while ripe fruit has yellowish green skin [5]. However, determining the ripeness of crystal guava fruit is difficult because of the similarity of color on the skin of the crystal guava fruit from raw to ripe. Determination of the ripeness of crystal guava fruit is uncertain because of the similarity of color on the skin of the fruit. This is why we need a method that can handle the uncertainty of determining the ripeness of crystal guava fruit. Fuzzy logic can solve problems that contain uncertainty [6].

A fuzzy Inference System is a rule system based on fuzzy logic. One method of fuzzy inference system is the Mamdani method. The Mamdani method or commonly known as the Min-Max method was first introduced by H. Mamdani in 1975. The Mamdani method is a method that uses the MIN implication function and the composition of the MAX rule. Fuzzy Mamdani is a fuzzy inference that is simple and easy to understand [7].

Many previous studies regarding the determination of fruit ripeness have been carried out, Mulato [8] conducted a study on the classification of red guava fruit ripeness using fuzzy Mamdani. The results obtained show a fuzzy accuracy of 83.3%. Lustini et al [9] also researched the classification of pineapple ripeness using fuzzy logic. The results obtained indicate an accuracy rate of 86.67%. Another study was conducted by Muthiati et al [10], who conducted a study on the detection of tomato ripeness. The ripeness level of the fruit is classified using fuzzy logic. Arief [11] conducted a study on the classification of citrus fruit ripeness. The fruits were classified based on color features using the SVM method. This research will determine the ripeness level of crystal guava fruit using fuzzy Mamdani. Crystal guava is categorized into four categories, namely raw, half ripe, ripe, and very ripe. It is hoped that by determining the ripeness of crystal guava fruit using fuzzy, the ripeness of the fruit can be more easily determined and more accurate.

2. RESEARCH METHODS

2.1 Data Collection

The first stage in this research is data collection. The image data used is 140 data consisting of 35 image data of crystal guava fruit in each category of ripeness level. Image data was taken with the Vivo Y30 smartphone camera with a white background.

2.2 Pre-Processing Data

In this step, the object and background are separated so that only the crystal guava fruit object is taken.

2.3 Feature Extraction

Image is one of the multimedia components that play an important role as a form of visual information. Image has characteristics that are rich in information. A digital image is a collection of pixels arranged in a matrix form. Each element in a digital image (element matrix) is referred to as a pixel (pixel) [12]. A color image or RGB image is an image in which each pixel has three color components, namely red (red), green (green), and blue (blue) components. Each color component has a pixel intensity value starting from 0 to 255. For example, a pixel that has a color intensity value of 255 in the red layer, 255 in the green layer, and 0 in the blue layer will produce a yellow color [13]. An illustration of an RGB image can be seen in Figure 1.

In this step, the crystal guava object image obtained from the previous stage is extracted by finding the average Red (R) value, Green (G) average value, and Blue (B) average value for each image pixel. These

values are used as inputs in the Mamdani fuzzy process.




Figure 1. RGB Image Illustration

2.4 Application of Fuzzy Mamdani

Fuzzy logic was first introduced by Prof. Lotfi Zadeh in 1965. Fuzzy logic is generally used to solve problems that contain an element of uncertainty. The level of true or false in fuzzy logic depends on the weight of the membership [14]. A fuzzy Inference System is a rule system based on fuzzy logic. One method of fuzzy inference system is fuzzy Mamdani. Fuzzy Mamdani or commonly known as the Min-Max method was first introduced by H. Mamdani in 1975. This method works based on linguistic rules.

In this step, fuzzy sets are formed and fuzzy rules are drawn up based on data training. The inputs used are Average Red, Average Green, and Average Blue variables, while the output used is ripeness level. There are four stages in the Mamdani fuzzy calculation, including:

a. Fuzzification

At this stage, the process of converting firm values (crisp) into fuzzy sets is carried out. The fuzzy set is grouped into a fuzzy variable based on its linguistic level. For each fuzzy set, the domain and membership function are determined which are then used to determine the membership value of each fuzzy set based on the input variables.

b. Application of The Implication Function

At this stage, the preparation of rules that state the relationship between input variables and output variables is carried out. The general form used to construct fuzzy rules can be written as follows [14],

$$\text{IF } (x_1 \text{ is } A_1) \text{ AND } (x_2 \text{ is } A_2) \text{ AND } \dots \text{ AND } (x_n \text{ is } A_n) \text{ THEN } y \text{ is } B \quad (1)$$

After forming the fuzzy rules, then determining the membership value based on the fuzzy rules that have been formed using the MIN implication function. By using AND operator, the results are obtained by taking the smallest membership value between elements in the set in question.

c. Composition of rules

At this stage, the process of merging the membership function from the applicable rules of the implication function is carried out. This merging process uses the MAX method. The fuzzy set solution is obtained by taking the maximum value of the rule, then using it to modify the fuzzy region and apply it to the output. If all the rules have been evaluated, then the output will contain a fuzzy set that describes the entire rule.

d. Defuzzification

Defuzzification is a process of converting fuzzy sets into crisp values. The input in the defuzzification stage is a fuzzy set obtained from the composition of the rules, while the output obtained is a number in the domain of the output variable fuzzy set. The method commonly used in the defuzzification stage is the centroid method (center point). In general, the centroid method can be written as Equation (2).

$$z^* = \frac{\int z \cdot \mu_A(z) dz}{\int \mu_A(z) dz} \quad (2)$$

2.5 Result Analysis


In this step, the results are validated by comparing the results of determining the level of fruit ripeness by farmers and the fuzzy program. The level of fuzzy accuracy used can be calculated by validating the results using the following Equation (3).

$$\text{Accuracy} = \frac{\text{appropriate data}}{\text{overall data}} \times 100 \quad (3)$$

3. RESULTS AND DISCUSSION

3.1. Pre-Processing Data

The data that has been collected, then separated the image of the fruit from the background, so that only the image of the crystal guava fruit object is taken. An example crystal guava fruit of the results of pre-processing data before the background separation can be seen in Figure 2 (a) and after the background separation can be seen in Figure 2 (b).



(a) Before the background separation; (b) After the background separation

Figure 2. The Results of Pre-Processing Data

3.2 Feature Extraction

Feature extraction is done to obtain the characteristics or information contained in an image or image. The image of the crystal guava fruit object that has been separated from the background is then extracted so that 3 information is obtained in the form of an average value of Red, an average of Green, and an average of Blue. This information is used as input to the fuzzy process. The value of the Red average, Green average, and Blue average are obtained from the calculation of the average Red value for each image pixel, the average Green value for each image pixel, and the average Blue value for each image pixel. Example of feature extraction results in Figure 2 (b) the value of Red Average = 121.1564, Green Average = 129.1392, and Blue Average = 45.1977.

3.3 Application of Mamdani Fuzzy

3.3.1 Fuzzy Set Formation

In this study, three inputs were used in determining the ripeness level of crystal guava fruit which included Red Average, Green Average, Blue Average, and one output in the form of fruit Ripeness Level. The formation of fuzzy sets is carried out on each variable. The Red Average variable is grouped based on its linguistic level into several fuzzy sets, namely low, medium, and high. Likewise for the Green and Blue variable average. Meanwhile, the Ripeness Level output variable is grouped into several fuzzy sets, namely raw, half ripe, ripe, and very ripe.

The fuzzy set that has been formed is then searched for the domain value in each fuzzy set. This domain contains values in the universe of speech, but can also be operated in fuzzy sets. Domains are determined based on training on the data used. In the data training process, the domain can be changed by shifting the domain value so that the correct domain is obtained for each fuzzy set used. Table 1 is a table for the formation of fuzzy sets and domains on the input variables. Table 2 is a table for the formation of fuzzy sets and domains on the output variables.

Table 1. Fuzzy Sets on the Input Variables

Variable	Fuzzy Set	Domain
Red Average (w)	Low	[0; 120]
	Medium	[62; 145]
	High	[120; 255]
Green Average (x)	Low	[0; 123]
	Medium	[75; 146]
	High	[123; 255]
Blue Average (y)	Low	[0; 55]
	Medium	[23; 73]
	High	[55; 255]

Table 2. Fuzzy Sets on the Output Variables

Variable	Fuzzy Set	Domain
Ripeness Level (z)	Raw	[0; 40]
	Half Ripe	[20; 60]
	Ripe	[40; 80]
	Very Ripe	[60; 100]


For each variable, its membership function is determined. The membership function is a curve that shows the mapping of input points into membership values with an interval of 0 to 1 [15]. The determination of the membership function in a fuzzy set can be different for each person. This is due to individual differences in expressing abstract concepts. However, the determination of the membership function must still reflect the issues discussed.

In this study, the membership function of the shoulder curve and the triangular curve were used to represent it. This form is suitable for representing fuzzy sets based on training on more accurate data. The Red Average variable consists of three low, medium, and high fuzzy sets. In the low and high Red Average variables, the left shoulder and right shoulder curve representations are used. The Red Average variable is being used as a triangular curve representation. The membership function for the Red Average variable is shown in Equations (4), (5), and (6). The membership function of the Red Average variable can be seen in Figure 2.

$$\mu_{Rrendah}(w) = \begin{cases} 1 & ; w \leq 62 \\ \frac{120-w}{58} & ; 62 < w < 120 \\ 0 & ; w \geq 120 \end{cases} \quad (4)$$

$$\mu_{Rsedang}(w) = \begin{cases} 0 & ; w \leq 62 \text{ atau } w \geq 145 \\ \frac{w-62}{58} & ; 62 < w < 120 \\ \frac{145-w}{25} & ; 120 \leq w < 145 \end{cases} \quad (5)$$

$$\mu_{Rtinggi}(w) = \begin{cases} 0 & ; w \leq 120 \\ \frac{w-120}{25} & ; 120 < w < 145 \\ 1 & ; w \geq 145 \end{cases} \quad (6)$$

**Figure 2. The Membership Function of the Red Average Variable**

The Green Average variable consists of three low, medium, and high fuzzy sets. The membership function for the Green Average variable is shown in Equations (7), (8), and (9). The membership function of the Green Average variable can be seen in Figure 3.

$$\mu_{Grendah}(x) = \begin{cases} 1 & ; x \leq 75 \\ \frac{123-x}{48} & ; 75 < x < 123 \\ 0 & ; x \geq 123 \end{cases} \quad (7)$$

$$\mu_{Gsedang}(x) = \begin{cases} 0 & ; x \leq 75 \text{ atau } x \geq 146 \\ \frac{x-75}{48} & ; 75 < x < 123 \\ \frac{146-x}{23} & ; 123 \leq x < 146 \end{cases} \quad (8)$$

$$\mu_{Gtinggi}(x) = \begin{cases} 0 & ; x \leq 123 \\ \frac{x-123}{23} & ; 123 < x < 146 \\ 1 & ; x \geq 146 \end{cases} \quad (9)$$




Figure 3. The Membership Function of the Green Average Variable

The Blue Average variable consists of three low, medium, and high fuzzy sets. The membership function for the Blue Average variable is shown in Equations (10), (11), and (12). The membership function of the Blue Average variable can be seen in Figure 4.

$$\mu_{B_{rendah}}(x) = \begin{cases} 1 & ; y \leq 23 \\ \frac{55-y}{32} & ; 23 < y < 55 \\ 0 & ; y \geq 55 \end{cases} \quad (10)$$

$$\mu_{B_{sedang}}(x) = \begin{cases} 0 & ; y \leq 23 \text{ atau } y \geq 73 \\ \frac{y-23}{32} & ; 23 < y < 55 \\ \frac{73-y}{18} & ; 55 \leq y < 73 \\ 0 & ; y \geq 73 \end{cases} \quad (11)$$

$$\mu_{B_{tinggi}}(x) = \begin{cases} 0 & ; y \leq 55 \\ \frac{y-55}{18} & ; 55 < y < 73 \\ 1 & ; y \geq 73 \end{cases} \quad (12)$$




Figure 4. The Membership Function of the Blue Average Variable

The Ripeness Level variable consists of four fuzzy sets: raw, half ripe, ripe, and very ripe. Raw and very mature Ripeness Level variables were used to represent the left and right shoulder curves. In the half-ripe and ripe Ripeness Level variables, a triangular curve representation is used. The membership function for the Ripeness Level variable is shown in equations (13), (14), (15), and (16). The membership function of the Ripeness Level variable can be seen in Figure 5.

$$\mu_{RL_{mentah}}(z) = \begin{cases} 1 & ; z \leq 20 \\ \frac{40-z}{20} & ; 20 < z < 40 \\ 0 & ; z \geq 40 \end{cases} \quad (13)$$

$$\mu_{RL_{setengahmatang}}(z) = \begin{cases} 0 & ; z \leq 20 \text{ atau } z \geq 60 \\ \frac{z-20}{20} & ; 20 < z < 40 \\ \frac{60-z}{20} & ; 40 \leq z < 60 \\ 0 & ; z \geq 60 \end{cases} \quad (14)$$

$$\mu_{RL_{matang}}(z) = \begin{cases} 0 & ; z \leq 40 \text{ atau } z \geq 80 \\ \frac{z-40}{20} & ; 40 < z < 60 \\ \frac{80-z}{20} & ; 60 \leq z < 80 \\ 0 & ; z \geq 80 \end{cases} \quad (15)$$

$$\mu_{RL_{sangatmatang}}(z) = \begin{cases} 0 & ; z \leq 60 \\ \frac{z-60}{20} & ; 60 < z < 80 \\ 1 & ; z \geq 80 \end{cases} \quad (16)$$




Figure 5. The Membership Function of the Ripeness Level Variable

3.3.2 Fuzzy Rules

After forming a fuzzy set, then determine the fuzzy rules. Fuzzy rules are indicated by the presence of a set of linguistic statements. The formation of fuzzy rules is based on the relationship between one set and another [16]. Based on Equation (1) and the data training that has been carried out, there are 27 fuzzy rules used in this study. Determination of fuzzy rules can be written as follows:

[R1] IF (Red Average is Low) AND (Green Average is Low) AND (Blue Average is Low) THEN (Ripeness Level is Raw),

[R2] JIKA (Red Average is Low) AND (Green Average is Low) AND (Blue Average is Medium) THEN (Ripeness Level is Raw),

etc. The overall rules used can be seen in Table 3.

Table 3. Fuzzy Rules

Rule	Input			Output
	Red Average	Green Average	Blue Average	Ripeness Level
[R1]	Low	Low	Low	Raw
[R2]	Low	Low	Medium	Raw
[R3]	Low	Low	High	Raw
[R4]	Low	Medium	Low	Raw
[R5]	Low	Medium	Medium	Half Ripe
[R6]	Low	Medium	High	Half Ripe
[R7]	Low	High	Low	Half Ripe
[R8]	Low	High	Medium	Half Ripe
[R9]	Low	High	High	Half Ripe
[R10]	Medium	Low	Low	Raw
[R11]	Medium	Low	Medium	Half Ripe
[R12]	Medium	Low	High	Half Ripe
[R13]	Medium	Medium	Low	Half Ripe
[R14]	Medium	Medium	Medium	Half Ripe
[R15]	Medium	Medium	High	Ripe
[R16]	Medium	High	Low	Half Ripe
[R17]	Medium	High	Medium	Ripe
[R18]	Medium	High	High	Very Ripe
[R19]	High	Low	Low	Ripe
[R20]	High	Low	Medium	Ripe
[R21]	High	Low	High	Very Ripe
[R22]	High	Medium	Low	Ripe
[R23]	High	Medium	Medium	Ripe
[R24]	High	Medium	High	Very Ripe
[R25]	High	High	Low	Very Ripe
[R26]	High	High	Medium	Very Ripe
[R27]	High	High	High	Very Ripe

3.3.3 Fuzzy Mamdani Calculation

Fuzzy sets and fuzzy rules have been formed based on data training, to make it easier to use using MATLAB software. The results obtained are then presented in the MATLAB GUIDE display. The program cannot directly determine the level of ripeness of crystal guava fruit. The user must input an image of a crystal guava fruit, then perform feature extraction, so that the Red Average (R), Green Average (G), and Blue Average (B) values are obtained as input in the Mamdani fuzzy process. After passing the Mamdani fuzzy

process starting from fuzzification to defuzzification, the output level of crystal guava fruit ripeness will be obtained. The MATLAB GUIDE display can be seen in Figure 6.




Figure 6. MATLAB GUIDE Display













In Figure 6, for example, there is an image of a crystal guava fruit after extraction, the average value of Red = 112.0645, Green Average = 120.4919, and Blue Average = 46.9704. The fruit image will be determined by the level of ripeness with the four stages in the fuzzy Mamdani. The four stages are as follows:

1. Fuzzification, at this stage, the low, medium, and high fuzzy set membership values are sought for each variable. In the fuzzy set, the average Red is low, the membership value is 0.13682, the average Red is 0.85318, and the red average is high at 0. The same is done for the fuzzy set with the average Green variable and the average Blue.
2. Evaluation, at this stage, each rule is evaluated using the MIN implication function by finding the smallest degree of membership between elements in each rule. At this stage the rules that have fuzzy areas are [R1], [R2], [R4], [R5], [R10], [R11], [R13], and [R14].
3. In composition, at this stage, the membership function of each rule is combined at the evaluation stage using the MAX method. The MAX method is carried out by taking the maximum value of the results of the evaluation of the rules in each fuzzy set of output variables. The results of the composition of the rules can be seen in the graph in Figure 6.
4. Defuzzification, at this stage the fuzzy set resulting from the composition of the rules is converted into a crisp value using the centroid method based on Equation (2). In this image, the final defuzzification value is 32.4825. The value obtained is then adjusted to the output linguistic variable. The results showed that the fruit was in the half-ripe category.

3.4 Result Analysis

In this study, validation results were carried out on 140 image data used. Validation is done by comparing the determination of the level of fruit ripeness between farmers and whether the program is appropriate or not. The validation of the results that have been carried out can be seen in Table 4.

Table 4. Validation Results

Data	Fruit Image	Extraction Image	Red Average	Green Average	Blue Average	Program Result	Description
001 Raw			64.0138	77.012	31.834	Raw	Correct
002 Raw			62.3598	74.9049	30.0887	Raw	Correct
003 Raw			63.7301	77.3829	31.9171	Raw	Correct
004 Raw			74.0377	82.3757	32.4553	Raw	Correct
005 Raw			65.8178	76.9513	24.5353	Raw	Correct
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
140 Very Ripe			121.1362	128.5469	60.1447	Ripe	Incorrect

Based on Table 4, the results obtained are 117 correct image data and 23 incorrect image data. The raw category of guava fruit image data that matched between farmers and the program amounted to 34 out of 35 raw category image data. The image data for the correct ripe category is 29. The image data for the ripe category is 27. The image data for the very ripe fruit category is 27. The fuzzy accuracy used can be calculated as follows:

$$Accuracy = \frac{117}{140} \times 100\% = 83.5\%$$

Determination of the level of ripeness of crystal guava fruit with four categories of ripeness levels raw, half ripe, ripe, and very ripe can be done using fuzzy Mamdani. The fuzzy set and fuzzy rules that have been formed can be applied to determine the ripeness level of crystal guava fruit with a fuzzy accuracy of 83.5%.

4 CONCLUSIONS

Determining the ripeness of crystal guava using fuzzy Mamdani is performed by extracting features on the fruit image and then forming fuzzy sets and fuzzy rules. The result of the feature extraction is in the form of a red, green, and blue average for each image pixel and is used as input for the fuzzy Mamdani process. The formed fuzzy sets are obtained through data training based on the results of feature extraction. 27 fuzzy rules are used. Verification of the results was performed with 140 test data, with 117 correct image data and 23 incorrect image data. As a result of the test, the fuzzy accuracy was 83.5%.

REFERENCES

- [1] D. Kurniawan, "Mengenal Jambu Kristal," Hortikutura, 16 Juni 2015. [Online]. Available: <http://hortikutura.pertanian.go.id/?p=354>. [Accessed 5 Oktober 2021].
- [2] S. Duryatmo, R. N. Apriyanti, S. Angkasa, A. A. Raharjo, K. Rizkika, D. S. Rahimah, A. Titisari, B. Setyawan, R. Vebriansyah, R. Fadhilah and K. R. Susilo, Jambu Kristal, Jakarta: Trubus, 2014.
- [3] D. Rustani and S. Susanto, "Kualitas fisik dan kimia buah jambu keistal pada letak cabang yang berbeda," *Bul. Agrohorti*, vol. 7, no. 2, pp. 123-129, 2021.
- [4] A. Wibowo, D. M. C. Hermanto, K. I. Lestari and Hadion, "Deteksi kematangan buah jambu kristal berdasarkan fiur warna menggunakan transformasi ruang warna HSV (Hue Saturation Value) dan K-Nearest Neighbour," *Journal of Informatic and Computer Science Engineering*, vol. 1, pp. 76-88, 2021.
- [5] A. Apriyantono, "Deskripsi jambu varietas kristal," *Varitas*, 13 September 2007. [Online]. Available: <http://varitas.net/dbvarietas/deskripsi/3136.pdf>. [Accessed 5 Oktober 2021].
- [6] S. Aly and I. Vrana, "Fuzzy expert marketing-mix model," *AGRIC*, vol. 51, no. 2, pp. 69-79, 2005.

- [7] E. F. Andriani, "Prediksi keuntungan PT. Ciesta Mandiri Sejahtera menggunakan Fuzzy Inference System Tsukamoto dan Fuzzy Inference System Mamdani," in *Fakultas Matematika dan Ilmu Pengetahuan Alam, Univeristas Jember*, Jember, 2015.
- [8] F. Y. Mulato, "Klasifikasi kematangan buah jambu biji merah (Psidium Guajava) dengan menggunakan model fuzzy," in *Fakultas Matematika dan Ilmu Pengetahuan Alam, Universitas Negeri Yogyakarta*, Yogyakarta, 2014.
- [9] A. Lustini, Saparudin and A. Primanita, "Klasifikasi tingkat kematangan buah nanas menggunakan ruang warna Red-Green-Blue dan Hue-Saturation-Intensity," *Jurnal Digital Teknologi Informasi*, vol. 2, no. 1, pp. 1-8, 2019.
- [10] N. N. Muthiati, Herlinawati, S. R. Sulistiyanti and S. Purwiyanti, "Deteksi tingkat kematangan buah tomat dengan metode fuzzy logic menggunakan modul kamera raspberry PI," *Jurnal Rekayasa dan Teknologi Elektro*, vol. 13, no. 2, pp. 38-42, 2019.
- [11] M. Arief, "Klasifikasi kematangan buah jeruk berdasarkan fitur warna menggunakan metode SVM," *Jurnal Ilmu Komputer dan Desain Informasi Visual*, vol. 4, no. 1, pp. 9-16, 2019.
- [12] R. Pratama, A. F. Assagaf and F. Tempola, "deteksi kematangan buah tomat berdasarkan fitur warna menggunakan metode transformasi ruang warna HIS," *Jurnal Informatika dan Komputer (JIKO)*, vol. 2, no. 2, pp. 81-86, 2019.
- [13] A. Pamungkas, "Pengolahan citra digital," Pemrogramanmatlab, 26 Juli 2017. [Online]. Available: <https://pemrogramanmatlab.com/2017/07/26/pengolahan-citra-digital/>. [Accessed 23 Mei 2021].
- [14] S. Kusumadewi and H. Purnomo, *Aplikasi Logika Fuzzy untuk Pendukung Keputusan*, Yogyakarta: Graha Ilmu, 2010.
- [15] B. Setiawan, B. Yanto and K. Yasdomi, *Logika Fuzzy dengan MATLAB*, Bali: Jayapangus Press, 2018.
- [16] L. N. Sari, "Penerapan logika fuzzy Mamdani dan manual kapasitas jalan Indonesia pada pengaturan lampu lalu lintas," in *Fakultas Matematika dan Ilmu Pengetahuan Alam, Univeristas Jember*, Jember, 2013.